

Desktop Info

by Glenn Delahoy



(C) Copyright 2005-2019
All rights reserved

Web Site: www.glenn.delahoy.com

Table of Contents

Description.....	5
License Agreement.....	5
Warranty.....	5
Technical Support.....	5
32 Bit Application.....	5
Windows Platforms.....	5
Application Priority.....	6
Process Access.....	6
A Note About Hardware Sensors.....	6
Donate.....	6
Usage.....	7
Context Menu.....	7
Windows Show Desktop.....	7
Command Line Options.....	8
Screen Saver.....	8
Windows Event Logs.....	8
Colors.....	8
Configuration File.....	10
Options Section.....	10
Text Section.....	14
Pages Section.....	14
Items Section.....	14
Formatting And Transformation.....	15
Formatting Numbers.....	15
Transforming Numbers.....	16
Formatting Dates.....	17
Formatting Times.....	18
Formatting Booleans.....	18
Bit Mapped Numbers.....	19
Languages.....	21
Character Sets.....	21
Right-To-Left Support.....	22
Language ID (LID).....	22
Item Options.....	24
Common Options.....	24
Thresholds.....	25
Charts.....	26
Bar Chart Colors.....	27
Data Logging.....	28
User Variables.....	28
Conditional Visibility.....	29
Item Reference.....	31
ALLIPADDRESS.....	31
BATTERY.....	31
BOOTTIME.....	31
COMMENT.....	32
CORETEMP.....	32
CPU.....	32
CPUCOUNT.....	32
CPUTEMP.....	32

CPUTYPE.....	33
CPUUSAGE.....	33
DATADUMP.....	33
DATETIME.....	33
DIRECTX.....	34
DISPLAYCONTROLLER.....	34
DNSSERVER.....	34
DOMAIN.....	34
DOMAINCONTROLLER.....	34
ENVVAR.....	35
EVENTLOG.....	35
FILE.....	35
FILE2TEXT.....	36
FILECONTENTS1.....	36
FILECONTENTS2.....	36
FILEEXIST.....	36
FIXEDDISK.....	37
HTTPGET.....	38
HOST.....	38
IEVERSION.....	38
IF.....	39
LOADTIME.....	39
NETCONNECTIONS.....	39
NETPACKETS.....	40
NETPACKETSRATE.....	40
NETWORKADAPTER.....	40
NETWORKINTERFACES.....	41
OEMINFO.....	43
OSBUILD.....	43
PAGEFAULTS.....	44
PAGEFILE.....	44
PHYSICALRAM.....	44
PROCESSCOUNT.....	44
PROCESSMEM.....	45
PROXY.....	45
RDSSESSIONID.....	45
REG.....	45
REGEXIST.....	46
REGISTRY.....	46
SERVICEPACK.....	47
SESSIONID.....	47
SET.....	47
TEXT.....	48
TIMEZONE.....	48
TOPPROCESSCPU.....	48
TOPPROCESSMEM.....	48
TOPPROCESSPF.....	49
TSSESSIONS.....	49
UNREADMAIL.....	49
UPTIME.....	49
USER.....	49
VIRTUALMEMORY.....	50

WMI.....50

Useful WMI Queries.....53

References.....56

Release Notes.....57

Version v1.13.0.....67

Description

This little application displays system information on your desktop. Looks like wallpaper but stays resident in memory and updates in real time. Perfect for quick identification and walk-by monitoring of production or test server farms or any computer you're responsible for. Everything is customisable (nearly).

License Agreement

This software is distributed free of charge. It may be used as many times as you like, for as long as you like, in a domestic or corporate environment. You may copy and distribute copies of this program provided that you keep all original documentation including this pdf file with copyright notice and disclaimer of warranty intact. You may not charge money or fees for the software product to anyone except to cover distribution costs.

Warranty

This program is provided "as is" without warranties of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The entire risk as to the quality and performance of the program is with you. Should the program prove defective, you assume the cost of all necessary servicing, repair or correction. In no event will the copyright holder be liable to you for damages, including any general, special, incidental or consequential damages arising out of the use or inability to use the program (including but not limited to loss of data or data being rendered inaccurate or losses sustained by you or third parties or a failure of the program to operate with any other programs).

Technical Support

No guarantees whatsoever are implied that technical support will be provided or that technical support, when provided, will be accurate. This software is basically unsupported and supplied on an as-is basis.

However there is a growing community at: www.glenn.delahoy.com/desktopinfo

32 Bit Application

This program is a 32 bit Windows application. It should run fine in any 64 bit environment with some restrictions. There will not be a native 64 bit version any time in the foreseeable future.

Windows Platforms

Desktop Info has been tested on the following Windows platforms:

Windows 2000 *

XP Pro (32 bit) version 2002 service pack 2

XP Pro (32 bit) version 2002 service pack 3

XP Pro (64 bit) version 2003 service pack 2

Vista (32 bit) business service pack 1
Server 2000 (32 bit) service pack 4
Server 2003 (64 bit) service pack 2

Server 2008 (32 bit) standard service pack 1
Server 2008 (64 bit) standard service pack 1
Server 2012 R2 (64 bit)
Windows 7 Professional 64 bit
Windows 8
Windows 10 Home/Pro 1709, 1803, 1809

* The program basically works on Windows 2000 but some items won't work.

Application Priority

The application is set to idle priority class as recommended by Microsoft which means that pretty much everything else will take priority but it won't necessarily wait until the cpu is idle.

Process Access

Some items may be denied access when retrieving data depending on the access rights of the user running it on Vista, 7, 8, 10 and others. Most of the time this can be overcome by running Desktop Info with Administrator privileges.

A Note About Hardware Sensors

Hardware sensors are problematic. The problem is manufacturers don't expose them to the operating system in a standard way. Windows provides standard WMI properties to be used by manufacturers but almost nobody implements them.

The only other approach is to laboriously study each manufacturer's hardware sensor implementation and write specific code for each one. This is not a path I wish to follow, better to leave that to a dedicated team of experts. There are a number of tools available to read hardware sensor information such as CoreTemp, Open Hardware Monitor, HWMonitor, Speedfan, Real Temp, Hardware Sensors Monitor, OCCT. I have implemented the CORETEMP item and hopefully I'll find another more complete tool that exposes an API.

I notice Windows 10 1803 is correctly showing CPUTEMP so I guess Microsoft is catching up.

Donate

Please show your appreciation for my hard work and long hours by making a donation. This will help keep the project alive and healthy. Donations of \$100 or more will be acknowledged on the Special Donors page on the web site to be set up shortly and also here in the manual. You can use PayPal, your debit or credit card or even Bitcoin. Go to www.glenn.delahoy.com/desktopinfo.

Usage

Just run it. You can kill it via the right click context menu or from Task Manager. Open the desktopinfo.ini file or select Configuration from the right click context menu and adjust each item in the items section to control visibility, refresh times, colors and other properties. The display updates itself automatically when you save the ini file.

Desktop Info ships with a sample desktopinfo.ini configuration file. The first time you run the application, the sample ini file will be copied to the working ini file. You are now free to modify it as needed using any text editor.

Context Menu

To get the context menu to appear in transparent mode, you have to right click on a visible pixel which may take a few tries. You can use the navigation buttons, a banner graphic or a bar chart. The context menu can be disabled by setting the 'contextmenu' item in the 'options' section to '0'.

Pages	Pages 1 to 9 are available depending on your configuration.
Show Desktop	In normal mode this minimises enough applications to make Desktop Info visible.
Refresh	This forces a refresh of the display and all items.
Configuration	Opens the current configuration file (desktopinfo.ini) in a text editor. When you save changes the configuration is reloaded.
Language	Opens the current language file in a text editor. When you save changes the configuration is reloaded.
Manual	Opens the manual with the default PDF reader.
Quit	Closes the Desktop Info application.

Windows Show Desktop

The Show Desktop button on the Windows Quick Launch toolbar and the WIN+D key combination makes every application including Desktop Info disappear. Apparently Windows actually puts the desktop on top of everything. Applications are not notified. There's nothing I can do about that.

Here are two options to overcome this:

If Desktop Info is partially visible, right click and select "Show Desktop". This will attempt to minimize enough applications to make itself visible.

Add a Desktop Info icon to your Quick Launch toolbar. When you run it, Desktop Info will look to see if it's running already. If it is, it will attempt to minimize enough applications to make itself visible. The obscuring windows may choose to ignore the minimize message or do other bizarre things which are outside of my control.

Command Line Options

The following command line options are available:

/f	Show a visible form. This tells Desktop Info to appear like a regular application with a frame allowing you to move it to the background or foreground and drag it around like any other application.
/ini	Specify the full path and file name to an alternative desktopinfo.ini file. desktopinfo.exe /ini=mynewwinifile.ini Don't forget the equals sign.

If there is one option on the command line with no '/' prefix, it is assumed to be an ini file. This way you can drag an ini file onto the exe file to start Desktop Info using that ini file.

Screen Saver

Desktop Info can be used as a screen saver. Make a copy of DesktopInfo.exe and rename it to DesktopInfo.scr. Right click on this file and select Install. In the ini file, the "ssfontsize" option controls the font size when running as a screen saver. The size and position is fixed. You can run the exe and the screen saver at the same time. Some items that work in normal mode when run as Administrator may not work in screen saver mode due to reduced privileges.

Windows Event Logs

In addition to it's own text file logging, you can make use of the Windows Event logs to monitor critical operations. Create an entry in the [options] section of the main ini file called "eventlog-level" and specify which logging events you want to be added to the event logs.

The available log levels are:

info	General application information
warn	When thresholds are triggered
error	Application or data errors

For example, to create an event log entry whenever a threshold is triggered or an error is raised:

```
eventlog-level=error warn
```

See also [Options](#).

Colors

Colors are specified in one of two ways:

BGR

A six character bgr (reverse rgb) hexadecimal number.

Think of this number as divided into three color elements, each element is a two digit number.

```
Color:BBGGRR
```

The first two digits represent the level of blue, the second represent the level of green, the third two represent the level of red.

RGB

A seven character rgb number. The first character is the hash symbol, '#', followed by a six character hexadecimal number.

Think of this number as divided into the prefix and three elements, each element is a two digit number.

```
Color:#RRGGBB
```

The hash prefix denotes rgb format, as opposed to the earlier bgr format, next is two digits that represent the level of red, two digits that represent the level of green and two digits that represent the level of blue.

Each color element has a range of 00-ff (or 0-255 in decimal). In bgr format, ff0000 is blue, 00ff00 is green, 0000ff is red. ffffff is white (all color elements at maximum), 000000 is black (all color elements are off). You can set each color element to any value between 00 and ff. Half way between fully off and fully on would be 80. If all three were set to half way, 808080, you would have a gray (grey) color.

If an item color is not defined it will take on the color of the previous item. In this way you can set the color for a block of items once for the first item and all successive items will be the same.

Google Color Picker

Go to Google and type in "color picker". This presents a simple color picker with a slider. On the left, you'll see the resulting hexadecimal color number with the hash ('#') prefix. Select a color you like by clicking on the main color area and using the slider then highlight the complete hexadecimal number on the left, including the hash prefix, and copy and paste this straight into your desktopinfo.ini file.

Configuration File

There is no configuration program. Options are set by modifying the ini file in a text editor such as Notepad. You can access the configuration from the right click context menu or directly using File Explorer. The ini file has four sections: Options, Text, Pages and Items. Each section contains a number of "key=value" entries.

Options Section

The following tables shows all options available in the [options] section.

Size And Position

monitor-mode	0 = single monitor mode 1 = virtual screen mode
monitor-num	monitor number (set monitor-mode=0)
top	Pixels down from the top
left	Pixels in from the left
bottom	Pixels up from the bottom
right	Pixels in from the right
width	Total width in pixels. If not specified then width is 400
centerv	Center vertically on the screen. 1 = centered 0 = not centered
centerh	If centerv is specified, top and bottom are ignored. Center horizontally on the screen. 1 = centered 0 = not centered
column1width	If centerh is specified, left and right are ignored. The width of column 1. -1 = automatic 0 = will effectively eliminate the column allowing the data column to occupy the whole space.

Desktop Info can view it's world from two different perspectives: single monitor mode and virtual screen mode.

Single Monitor Mode is the default mode. It's world consists of just the selected monitor. The origin (top=0 left=0), therefore, is the top left of the selected monitor. You cannot place DTI outside of the boundaries of the selected monitor regardless of the values you put in the top/left/bottom/right options. Using the monitor-num option, you can select which single monitor DTI lives in. 0 is the primary monitor, 1 is the secondary monitor etc.

So, to always have DTI on the primary monitor, set monitor-mode=0 and monitor-num=0 (this is the default). To force DTI to always be on the secondary monitor, set monitor-mode=0 and monitor-num=1.

In Virtual Screen Mode, Desktop Info views it's world in terms of the Windows virtual screen. In this world the screen is an imaginary rectangle that encompasses all monitors connected to the

system, regardless of their relative position. The origin (top=0 left=0) is the top left of this imaginary rectangle. In Virtual Screen Mode, the monitor-num option is not used.

Note: In version 1.11, the origin was always the primary monitor and therefore it was necessary to set values outside of the primary monitor. This is no longer the case, values now are always greater than or equal to zero and less than or equal to the width/height of either the single monitor or the virtual screen.

It is useful to note that if, like me, your laptop is in and out of the dock, DTI will automatically reset it's position according to the updated Windows display configuration. So, for example, I have a secondary monitor attached to the dock and configured to be above the laptop display. With DTI set to monitor-mode=1 top=0 right=0, it positions itself at the top right of the laptop display when it is out of the dock and the top right of the secondary monitor when it is in the dock.

Here are additional rules for the position options:

- if left is specified, it is left aligned
- if right is specified, it is right aligned
- if both are specified, it is left
- if neither then right=0

- if top is specified, it is top aligned
- if bottom is specified, it is bottom aligned
- if both are specified, it is top
- if neither then top=0

Interface

formcolor	Background color (bgr)
transparency	Background transparency. 0 = opaque 100 = totally transparent.
contextmenu	Enables the right click context menu 0 = disabled 1 = enabled
allowdrag	Enables the ability to drag the form. If the /f option is used the form is always draggable. 0 = disabled 1 = enabled
nav	Enable the navigation buttons 0 = disabled 1 = enabled
nav-align	Horizontally align the navigation buttons -1 = align left 0 = align center 1 = align right
nav-color	Navigation buttons color (bgr)
language	File name containing language override settings. See Language File section for more information.

The optional navigational buttons may be enabled using the "nav" option. They appear below the last item and may be aligned left, center or right using the "nav-align" option.

You can adjust the DTI transparency using the 'transparency' option. A value of 100 is totally transparent, a value of 0 is opaque. You can also set the background color of a partially transparent form using the 'formcolor' option.

There is just one caveat to the colors: because Windows requires that I select a color to act as the transparent color, I chose black. This means if you set any of the items to be black color, they will become transparent. You should instead use '000001' or some other color that is close enough to black.

Font

font-face	the name of the font face
font-size	the size of the font, default is 8, minimum is 6
font-charset	the character set for the font
font-rtl	Right To Left support. 1=rtl enabled, 0=left to right. This is obviously designed for right-to-left languages but there's no reason why you can't use this in Latin languages.
cleartype	enables/disables ClearType for the font
ssfontsize	the font size in screen saver mode
line-spacing	the number of pixels between each text row. Can be positive or negative. default=2

Banner Graphic

Optional graphic at the top of the display. The image must be png format.

logo	png graphic file to display at the top of the Desktop Info display logo=<filename>
logo-width	stretch the image to this width 0 = maintain the width of the original image -1 = stretch to the width of the form
logo-height	stretch the image to this height 0 = maintain the height of the original image -1 = stretch to the height of the form
logo-align	horizontal positioning relative to the form width -1 = align left 0 = align centre 1 = align right

Application Logging

log	Write application logging information to the specified log file.
log-level	info = general information messages

	error = application or data errors
	warn = thresholds
	debug = for tracking down application issues
	data = displayed data output
	debugonerror = start debug logging for a short time after an error is raised
eventlog-level	Write entries to the Windows Application event log
	info = general information messages
	error = application or data errors
	warn = thresholds

DesktopInfo64

Tool used to retrieve 64 bit counters and other metrics not available to a 32 bit application.

desktopinfo64	Enable the 64 bit tool
	0 = disabled (default)
	1 = enable

Why do we need 64 bit counters? Desktop Info is a 32 bit application. In nearly every case this is fine. In a few cases this has been a barrier to retrieving accurate counters. DesktopInfo64 is a small 64 bit application that performs these tasks in a separate process and passes the results back to the main application.

The items that this tool handles are TOPPROCESSMEM and PROCESSMEM. In both cases because a 32 bit number has a maximum value of 4GB and some big processes can consume more than 4GB of memory. Using the 64 bit tool enables values greater than 4GB to be retrieved from the counters.

Also, in the case of PROCESSMEM, Windows does not return private usage to 32 bit applications so the 64 bit tool is able to retrieve that counter.

When enabled, desktopinfo64 is started automatically when Desktop Info starts and shut down when Desktop Info shuts down. It will inherit access permissions so if Desktop Info is run as Admin, then desktopinfo64 is also run as admin.

Other

inimonitortime	How often to check for desktopinfo.ini changes.
text-editor	Full path and file name to your preferred text editor. Called when you open the configuration and language files from the context menu.
text-align	Set the alignment of the left column item title text, excluding COMMENT, FILECONTENTS2 and FILE2TEXT. See also font-rtl option. 0 = left aligned (default) 1 = right aligned

Text Section

noresults	text to display when an item returns no results
error	text to display on screen and in log file when an error occurs

Pages Section

You can configure up to 9 pages of data to be available for viewing from the right click context menu and the navigation buttons. This is a neat way of grouping information together, providing a summary on the first page and more detailed info on other pages.

The pages section allows you to configure the page titles. Give each page whatever title you want. A blank title will disable that page. Page 1 cannot be disabled.

```
[pages]
1=Main Page
2=Windows / Hardware
3=
4=
5=
6=
7=
8=
9=
```

Use the 'active' option for each data item to configure which page that item will appear on.

For example, to make an item appear on the first page, set "active:1". To make an item appear on the second page, put "active:2". On the ninth page, put "active:9".

DTI only collects data for the currently visible page. When you change the page the data will begin collecting for that page.

Items Section

The items section in the ini file controls the order and state of each info item. Each item consists of an ID followed by a comma delimited list of key:value options.

See the [Item Options](#) section for more information.

The complete list of available items is in the [Item Reference](#) section.

Formatting And Transformation

Formatting Numbers

Any item that displays a number can be formatted in the 'display' template property. You specify the replaceable parameter for the value you want (refer to the item reference) and follow it with the number format option. The general form of the number format is:

```
%1[w.pt]
```

This is the replaceable parameter representing the value you want to display immediately followed by exactly four characters inside square brackets. The first character 'w' is a single digit that defines the maximum width of the number. The second character is a dot. The third character 'p' is a single digit that defines the precision of the number. That is, the number of places after the decimal point. The fourth character 't' defines the type of number.

The four general number types are:

d	decimal	w = minimum width left padded with zeros, p=not used
f	float	w = minimum width left padded with spaces, p=decimal places
n	float	same as 'f', commas inserted for thousands
x	hexadecimal	w = minimum width left padded with zeros, p=not used

In this case, decimal means integer, a whole number, float means a number that may not be a whole number. Hexadecimal can only be used on integer type numbers.

So a simple example is:

```
display:%1[3.0d]
```

This displays the first value with no decimal place, a minimum 3 characters wide, left padded with zeros. Eg "005" or "016" or "000" or "83738"

Example:

```
display:%2[5.0d]
```

This displays the second value with no decimal place, a minimum 5 characters wide, left padded with zeros. Eg "00040" or "00597" or "00000"

Example:

```
display:%3[4.1f]
```

This displays the third value with 1 decimal place, a minimum 4 characters wide, left padded with spaces. Eg "12.5" or "9.0" or "0.1"

Example:

```
display:%1[7.0n]
```

This displays the first value with no decimal places, a minimum 7 characters wide, commas inserted for thousands, left padded with spaces. Eg "123,456" or " 3,654" or " 67"

Transforming Numbers

Sometimes it's useful to change a number from thousands of things to kilothings or megathings or gigathings. This is usually bytes but it doesn't have to be. Formatting types are available to help transform these values.

These also follow the rules for the 'f' number type. Width excludes the units in the case of 'b' or 'B'.

Note: There is a difference between binary bytes and decimal bytes. Binary bytes are powers of 2. So a kilobyte is 1024 bytes. Decimal bytes are powers of 10. So a kilobyte is 1000 bytes. Make sure you choose the correct transform option for the data. For example, most hard drive manufacturers quote their drive size in decimal bytes, Windows quotes memory in binary bytes.

See also: <https://en.wikipedia.org/wiki/Kilobyte>

In the following table, binary transformations use the lower case number type, decimal transformations use the upper case number type.

k K	convert to kilo	w = minimum width left padded with spaces, p=decimal places
m M	convert to mega	w = minimum width left padded with spaces, p=decimal places
g G	convert to giga	w = minimum width left padded with spaces, p=decimal places
t T	convert to tera	w = minimum width left padded with spaces, p=decimal places
b B	best fit convert	w = minimum width left padded with spaces, p=decimal places, append unit

Example:

```
%3[1.0k]
```

Displays the third value, binary converted to kilothings, no decimal places, a minimum of 1 character wide. eg "4" or "0" or "4567"

Example:

```
%3[3.1M]
```

Displays the third value, decimal converted to megathings, 1 decimal place, a minimum of 3 characters wide. eg "4.1" or "12.0" or "1483.6" or "0.5"

Example:

```
%3[3.1b]
```


Displays the third value, binary converted using best fit, 1 decimal place, a minimum of 3 characters wide, unit appended. eg "6.1Ki" or "6.5Mi" or "1.1Gi"

If that was a decimal transform:

```
%3[3.1B]
```

Displays the third value, decimal converted using best fit, 1 decimal place, a minimum of 3 characters wide, unit appended. eg "6.1K" or "6.5M" or "1.1G"

You add your own 'thing' after the number. Example:

```
%3[3.1b]B
```

Displays the third value, binary converted, "6.1KiB"

or

```
%3[3.1B]B
```

Displays the third value, decimal converted, "6.1KB"

Formatting Dates

The following can be used to help format dates:

[ddd]	short day name
[dddd]	long day name
[mmm]	short month name
[mmmm]	long month name
[yy]	last two digits of the year
[yyyy]	four digit year

Example:

```
%1[ddd]
```

The first value is the day of the week. It can be displayed as a normal number or formatted to show the short day name. eg "Mon" "Tue"

Example:

```
%1[dddd]
```

The day of the week can be displayed as a long day name. eg "Monday" "Tuesday"

Example:

```
%1[dddd] %2 %3[mmmm] %4[yyyy]
```

This will display the first four values of DATETIME. eg "Thursday 6 September 2018"

Example:

```
%1[ddd] %2 %3[mmm] %4[yy]
```

This will display DATETIME as "Thu 6 Sep 18".

Formatting Times

If you want a basic 24 hour display, the regular number format would work:

```
%5[1.0d]:%6[2.0d]:%7[2.0d]
```

Will display something like "9:24:45" or "13:15:01"

To format a 12 hour display there are a few additional format options:

[1.0a]	convert the hour to 12 hour, ie any value from 13 to 24 is reduced by 12
[2.0p]	show 'am' or 'pm' depending on the hour in the value
[2.0P]	show 'AM' or 'PM' depending on the hour in the value

Example:

```
%5[1.0a]:%6[2.0d]:%7[2.0d] %5[2.0P]
```

This will display DATETIME as "9:24:45 AM" or "1:15:01 PM". Notice that the last parameter is the hour (%5) but in this case is being used to decide how to display the AM or PM.

Example:

```
%5[1.0a]:%6[2.0d]:%7[2.0d] %5[2.0p]
```

This will display DATETIME as "9:24:45 am" or "1:15:01 pm".

Formatting Booleans

Boolean values can have 1 of only 2 possible values: 1 or 0, true or false, yes or no, on or off etc. In WMI land, booleans tend to be displayed as True or False. Sometimes it makes sense to display these values using normal everyday language. To convert boolean values into words use the following format:

```
[b:true:false]
```

In the place of the word 'true', you put whatever text you want. The same with the word 'false'. The correct text will be displayed based on the value of the boolean number.

In the following example, Win32_ComputerSystem has two properties relating to daylight savings. These can be displayed meaningfully thus:

Example:

```
display:Enabled: %EnableDaylightSavingsTime%[b:Yes:No]\, In Effect: %DaylightInEffect%[b:Yes:No]
```

This will display something like "Enabled: Yes, In Effect: No".

Bit Mapped Numbers

There are some WMI classes that return multiple results in a single number. We call these "bit mapped" numbers. For example, the AntiVirusProduct class in the root\SecurityCenter2 namespace has a property called productState that is a single integer value. Each binary 'bit' in that integer represents some information like 'enabled' and 'up to date'. We can extract this information by performing a bit-wise AND operation.

Desktop Info achieves this using the following display format:

```
[bit:value:true:false]
```

This is very similar to the boolean format except we want to know if a given bit is on in the returned property value. The 'value' is the decimal value of the bit you want to examine. In the place of the word 'true', you put whatever text you want. The same with the word 'false'. Desktop Info performs the bit-wise AND operation with the 'value' and the returned property value. If the result is not zero, the 'true' text is displayed, if the result is zero, the 'false' text is displayed.

In the case of the AntiVirusProduct example, the WMI query will look like this:

```
WMI=active:1,text:AV,namespace:root\  
SecurityCenter2,query:AntiVirusProduct,display:%productState%
```

This will show a number something like 397312 or 393216. This is not very useful. Now we add the display format:

```
display:%productState%[bit:4096:Enabled:Disabled]
```

The display will now show text depending on whether the given bit is on or off..

```
AV           Enabled
```

or

```
AV           Disabled
```

There is another bit field in that number we can make use of which is the 'up to date' field. The decimal value for this field is 393216. The display format will look like:

```
display:%productState%[bit:393216:up to date:not up to date]
```

The display will show text depending on whether that bit is on or off (it's actually two bits but that matters not):

```
AV           up to date
```

or

```
AV           not up to date
```

Finally, we can combine these two in the display format thus:

```
display:%productState%[bit:4096:Enabled:Disabled] and %productState%  
[bit:393216:up to date:not up to date]
```

This will result in a display something like:

AV	Enabled and up to date
----	------------------------

or

AV	Enabled and not up to date
----	----------------------------

or

AV	Disabled and not up to date
----	-----------------------------

Languages

The language file allows you to override text and display options set in the desktopinfo.ini file. It essentially mirrors the main ini file with the exception of the actual item configuration. You don't have to supply every configuration option again in the language file, just specify the ones you want to be different from the main ini file.

All options in the [options] section can be overridden as required. If you override the [pages] section you should specify all pages even if they are blank. I haven't got multi-byte text on the menu options yet, your mileage will vary.

In the language file, the [items] section contains a list of 'text' values that will override the item text in the main ini file. Add just the item entries you want to override. Each item is a name=value pair where the name matches either the item id or the item lid in the main ini file and the value is any text you want to use on the title display for that item.

The NETWORKADAPTER, FIXEDDISK and CPUUSAGE items may contain '%1' which will be replaced by the instance number.

Desktop Info is able to display multi-byte and right-to-left languages although there is still work to be done in that area. If your language is a multi-byte language, it's important the language text file is UTF-8 encoded so that the text is correctly stored and read back and the font options are correctly specified.

To successfully display multi-byte languages you need the following things:

- Specify a language file in the desktopinfo.ini file
- The language file must be UTF-8 encoded
- In the language file, specify the "font-face" option with a font capable of displaying your language
- In the language file, specify the "font-charset" option with a character set within the font
- In the language file, specify the "font-rtl" option if your language is right-to-left

Desktop Info comes with a number of sample language files found in the "sample-languages" directory in various degrees of translation completion. If you decide to use one of the sample language files, you should copy it to a new location first to avoid it being overwritten by the next new version. Some of the sample language files are supplied by volunteers for which I am grateful while some are constructed from Google Translate so I don't expect they will be wonderful translations. If you see any errors please let me know so I can correct them for future releases.

Character Sets

If you wish to display a language that is different to your current Windows locale, you may need to set the "font-charset" option in your language file so the correct character set is used for display. Latin based languages normally use the Ansi character set.

For example, to set the character set to display simplified Chinese:

```
font-charset=134
```

This is the list of available character sets from which you can choose.

0	ANSI_CHARSET	ANSI characters
1	DEFAULT_CHARSET	Font is chosen based solely on Name and Size. If the described font is not available on the system, Windows will substitute another font.
2	SYMBOL_CHARSET	Standard symbol set.
77	MAC_CHARSET	Macintosh characters.
128	SHIFTJIS_CHARSET	Japanese shift-JIS characters.
129	HANGEUL_CHARSET	Korean characters (Wansung).
130	JOHAB_CHARSET	Korean characters (Johab).
134	GB2312_CHARSET	Simplified Chinese characters (mainland china).
136	CHINESEBIG5_CHARSET	Traditional Chinese characters (Taiwanese).
161	GREEK_CHARSET	Greek characters.
162	TURKISH_CHARSET	Turkish characters.
163	VIETNAMESE_CHARSET	Vietnamese characters.
177	HEBREW_CHARSET	Hebrew characters.
178	ARABIC_CHARSET	Arabic characters.
186	BALTIC_CHARSET	Baltic characters.
204	RUSSIAN_CHARSET	Cyrillic characters.
222	THAI_CHARSET	Thai characters.
238	EASTEUROPE_CHARSET	Includes diacritical marks for eastern European countries.
255	OEM_CHARSET	Depends on the code page of the operating system.

Right-To-Left Support

Desktop Info supports Right-To-Left languages. In addition to the "font-charset" option above, add the following option to your language file:

```
font-rtl=1
```

Language ID (LID)

If you want to override text for an item that does not have a unique ID, you will need to specify a 'lid' for the item. That is, where the ID appears more than once in the main ini file such as COMMENT, WMI etc. If the ID is unique then that can be used in the language file.

So, to override an item you know to be unique, such as CPUTEMP, just add an entry to the language file [items] section with that key and the text you want.

```
CPUTEMP=Température du Cpu
```

If the item ID is not unique, such as COMMENT, add the "lid" option to the item in the main ini file:

```
COMMENT=active:1,text:Desktop Info,lid:banner
```

Now add an entry with that key to the language file [items] section:

```
banner=Infos sur le bureau
```

You can have multiple instances of any item, for example you might put DATETIME on each page. In this case you don't need to have a unique language id because the text you define in the language file for the DATETIME item would apply to all instances of the item.

You should ensure the language file is UTF-8 encoded for multi-byte compatibility.

To enable the new language add the 'language' entry to the [options] of desktopinfo.ini pointing to your language file.

```
language=french.ini
```

Item Options

Common Options

The following table lists options common to all items. In addition, each item will define it's own options detailed in the [item reference](#).

<u>key</u>	<u>value</u>
active	a value of 0 is off, 1 or more is active on that page number
hidden	Item is active on the page given by the “active” option but will not display
interval	The refresh interval in seconds where 0 means never refresh after the first time
lid	Language id. This provides a unique id for a specific item where there may be multiple instances of the same id such as COMMENT or WMI, in order to get the correct entry in the language files.
color	A bgr value as described in the Colors section. If not specified, the item takes the color of the previous item.
style	Font style where b = bold, i = italic, u = underline, w = full width underline
csv	Output data to a csv file
csvdatatype	0=raw data, 1=display data
threshold1, threshold2, threshold3	up to 3 thresholds may be defined for each item
chart	Display a bar or line chart as described in the Charts section.
bar-colors	Bar chart colors in bgr or rgb form as described in the Bar Chart Colors section.
text	Set your own item title text
set	Save the display output to the given user variable
display	Template for the item display
text-offset	Offset the left column text from the left margin (or the right if you have text-align or font-rtl set.

The visibility of each item is controlled by the ‘active’ value. If the active value of an item is set to ‘1’ the item will be visible on the first page. If the active value is set to ‘2’ the item will be visible on the second page. If you don’t specify an item at all, it will not display. Change the page currently being displayed from the right click context menu or navigation buttons.

An example is:

```
DATETIME=active:1,interval:1,color:ffffff
```

where the datetime item is displayed on page 1, refreshed every second and the color is white.

Some items such as NETWORKADAPTER and FIXEDDISK control all instances. For example, if you switch on FIXEDDISK, all fixed disks are displayed including most usb disks.

The children of the NETWORKADAPTER and FIXEDDISK items have a default *text-offset* of 10 pixels.

Each item has a list of available values you can display. To display a value, put its replaceable parameter in the display template option along with any other text you want to include in the display. Refer to the [Item Reference](#) to see what replaceable parameters are available.

Example: the CPU item returns two values: cpu and kernel. To display these use %1 for the cpu value and %2 for the kernel value.

```
display:Tot: %1 Krnl: %2
```

Will display something like:

```
Tot: 5 Krnl: 2
```

If you want to use a comma in a text or display property, you must precede it with a backslash.

Incorrect Use Of A Comma

```
display:Receive:%1 bps, Transmit:%2 bps
```

Correct Use Of A Comma

```
display:Receive:%1 bps\, Transmit:%2 bps
```

Each WMI item will have as many replaceable parameters as there are properties in the result set. The replaceable parameter is the name of the property enclosed in percent signs.

Thresholds

Any item that displays a numerical value may be configured to change color when that item reaches or exceeds a given value. It could be an absolute value such as PAGEFAULTS or DISKQUEUE, it could be a percent such as CPU or PHYSICALRAM or a rate such as NETPACKETSRATE or DISKIO.

The general form of the threshold option is:

```
threshold#:num tvalue color
```

Where:

threshold#	one of 'threshold1', 'threshold2' or 'threshold3'
num	any of the returned values for the item
tvalue	threshold value that will cause the color to change
color	the new color of the item

Example: The CPU item has two return values: the cpu percent and the kernel percent. To define a threshold for the first value:

```
threshold1:1 90 0000ff
```

This means use the first return value, trigger at 90 (percent), the new color is red. I could have assigned this to threshold2 or threshold3, it doesn't matter.

I could define a second threshold to handle the kernel percent:

```
threshold2:2 50 0066ff
```

This uses the second return value, trigger at 50 (percent), the new color is orange.

Put both of these on the CPU item:

```
threshold1:1 90 0000ff,threshold2:2 50 0066ff
```

For WMI queries you need to know the order of the returned properties to determine the number of the property you want. WMI Explorer is your friend.

To define a threshold which triggers when the raw value drops below a value, specify a negative threshold value. For example, the BATTERY item would have a threshold like this:

```
threshold1:1 -20 0000ff
```

Where the threshold triggers when the battery charge falls to 20% or less.

Charts

Any numerical value can be charted. You can use either the bar chart or line chart with a linear or logarithmic scale. To work out what you want to chart, look at the list of returned values in the item reference.

The general form for the bar chart option is:

```
chart:bar scale max series [[-]tvalue]
```

Where:

bar	displays the bar chart
scale	'linear' = linear scale 'log' = logarithmic scale
max	maximum value of the chart
series	the number of a return value to display
tvalue	threshold value of the bar chart (optional)

If the threshold, tvalue, is a positive value, the bar will change color as the value increases towards that value, a 'disk used' gauge for example. If the threshold is a negative value, the whole bar will change color when the value decreases to that value or below, a battery gauge for example.

See also, the [Bar Chart Colors](#) section below.

The general form for the line chart is:

```
chart:line scale max series1 color1 [series2 color2]
```

Where:

line	displays the line chart
scale	'linear' = linear scale

	'log' = logarithmic scale
max	maximum value of the chart
series1	the number of a return value to display
color1	color of series1
series2	the number of a return value to display (optional)
color2	color of series2

Example: A simple battery gauge:

```
chart:bar linear 100 1
```

A bar chart, linear scale, maximum value of 100 (percent), using the first return value which is percent charge remaining.

You can have the bar change to red when it drops to a certain critical value:

```
chart:bar linear 100 1 -20
```

The negative threshold tells the bar to change color when the value drops below 20%.

Example: Cpu chart:

```
chart:line linear 100 1 00ff00 2 0000ff
```

A line chart, linear scale, a maximum value of 100, the first series uses the first return value (cpu percent) and has a color of green, the second series uses the second return value (kernel percent) and has a color of red.

Logarithmic scales apply a log base 2 calculation to the value before charting it. This transforms a value of 1000 to about 10, a value of 10000 to about 13. This allows you to have sensible charts ranging from zero to huge numbers such as disk transfer speeds or network speeds. For a network speed chart with typical speeds of 10MiBps you would have a log chart with a maximum value of around 26. For a throughput of 1GiBps you would have around 30. For more information, Google is your friend.

For WMI queries you need to know the order of the returned properties to determine the number of the property you want. WMI Explorer is your friend.

Line charts always consume two rows below the item result text but bar charts are normally appended to the end of the result text display. If the display text is long the bar chart can be tiny. You can shift the bar chart on to the next row by adding two pipe symbols to the end of the display template:

```
PHYSICALRAM=active:5,interval:5,color:ffd0e0,threshold1:3 80
0000FF,chart:bar linear 100 3 80,display:%1[3.1b]B / %2[3.1b]B (%3%
used) ||
```

Bar Chart Colors

You can define custom colors for the bar charts. There are three colors:

chart area	default color
below threshold	green
threshold	orange
above threshold	red

Use the *bar-colors* common option to define the three colors in either 6 character bgr form or 7 character rgb form separated by spaces.

For example, the CPU item might have a bar chart defined:

```
CPU=active:1,chart:bar linear 100 1 80
```

Add the bar-colors option thus:

```
CPU=active:1,chart:bar linear 100 1 80,bar-colors:ff0000 0000ff 00ff00
```

This will set the three colors to blue, red and green respectively.

Data Logging

You can log individual items by adding 'csv:filename'. For example:

```
csv:c:\cpu.csv
```

This writes the data to a csv formatted file where the cells are enclosed in quotes and separated by commas and the first row contains column identifiers.

By default, the data is written in it's raw form. You can write the formatted data by adding 'csvdatatype:1'.

This example writes raw data to a file in the root directory:

```
PAGEFAULTS=active:1,interval:10,csv:\pagefaults.csv
```

This example writes formatted data:

```
PAGEFAULTS=active:1,interval:10,csv:\pagefaults.csv,csvdatatype:1
```

User Variables

User variables are a way to store data and text so that it can be used later. There are two ways to set a user variable:

1. Using the "set" parameter in any item. For example:

```
HOST=active:2,interval:0,set:hostname
```

stores the display of the HOST item in a variable called "hostname". The item must be active.

2. Using the SET item you can store anything you can type in. For example:

```
SET=active:2,key:MyTestKey1,value:MyTestValue1
```

stores the value of "MyTestValue1" into a variable called "MyTestKey1".

Having stored these values into user variables, you can display them using any item's display by typing the variable name enclosed in percent signs. For example:

```
TEXT=active:1,interval:0,text:Host/User,display:%hostname%/%username%
```

displays the "hostname" and "username" variables together on a single line.

```
Host/User          DESKTOP-PC/Glenn
```

This is the complete example.

```
HOST=active:9,interval:0,set:hostname
```

```
USER=active:9,interval:0,set:username
```

```
TEXT=active:1,interval:0,text:Host/User,display:%hostname%/%username%
```

Here's the same thing done a slightly different way. It does the USER item first and stores that result then does the HOST item and displays both at once.

```
USER=active:9,interval:0,set:username
```

```
HOST=active:1,interval:0,text:Host/User,display:%1/%username%
```

Here's another example. It combines boot time and up time into a single line display. Notice both the UPTIME interval and the TEXT interval are set so it continues to update.

```
UPTIME=active:9,interval:1,set:uptime,display:%1d :%2h :%3m :%4s
```

```
BOOTTIME=active:1,interval:1,display:%1 (Up: %uptime%)
```

In this example we want to read a small text file containing important information that gets updated by the domain admin. First we monitor the file for changes, read the first line into a user variable then display that variable. In this case it's the support extension number that changes daily. It could be asset or other information the domain support people want to push out to computers.

```
FILE=active:9,interval:60,type:text,text:Contact,file:\contact.txt,set:supporttext
```

```
TEXT=active:1,interval:60,text:Support,display:Call Glenn on ext %supporttext%
```

An interesting thing to note is the TEXT item itself can have the set parameter. This means you can cascade user variables or build them from other variables. If you can find a use for this I'm listening.

Conditional Visibility

You can control an item's visibility using User Variables and the IF item. You use the IF item to compare two values, if the comparison returns true the following item is displayed, if the comparison returns false the following item is not displayed. The two values can be user variables, numbers or literal character strings.

For example, if the BATTERY item returns no result (ie there's no battery), then you don't need to display it. To achieve this, you run the BATTERY item using the 'hidden' option and the 'set' option. Then you use an IF item to compare that result with the "noresults" text string. On the next line you use a TEXT item to display the results of the BATTERY item. If the IF comparison returned true the TEXT item is displayed, otherwise it is skipped.

```
BATTERY=active:1,interval:60,set:battery,display:%1%,hidden:1
IF=active:1,value1:%battery%,value2:<n/a>,comparator:ne
TEXT=active:1,interval:60,text:Battery,display:%battery%
```

See the [IF](#) item for available options.

Item Reference

The following is a complete reference of available items and their options and return values. See also the list of [common options](#).

Return values are listed as replaceable parameters; use these in the display template property to display these values. See the formatting section earlier for more information and the sample ini file for examples. Any item that returns a numerical value can be charted and have thresholds. Use the item return value numbers for the chart and threshold series.

ALLIPADDRESS

Shows all IP addresses assigned to all interfaces.

Available Options:

multirow	0=comma delimited on a single line 1=one ip address per line
----------	---

Return Values:

%1	ip address
%2	subnet mask
%3	prefix length

BATTERY

Shows laptop battery status.

Return Values:

%1	estimated charge remaining percent
%2	battery status numeric
%3	battery status message

BOOTTIME

Shows the time of day the host was booted.

Return Values:

%1	day of week
%2	date
%3	month
%4	year
%5	hours
%6	minutes
%7	seconds

COMMENT

Allows you to put any fixed text on the display. Makes a nice banner and section header. You can also use this to create a blank line to visually separate blocks; just create a COMMENT item with no text.

Available Options:

text	Text to display over both columns
------	-----------------------------------

CORETEMP

This item reads the shared memory area of Core Temp. This tool must be running, visible or hidden, for Desktop Info to interact with it. Desktop Info does not need to be run as administrator using this approach. Best of all it's much more likely to succeed on any computer than the WMI method.

Get Core Temp at: <http://www.alcpu.com/CoreTemp/>

Hint: Pay attention during the installation process!

Return Values:

%1	Temperature
----	-------------

CPU

Shows percentage of all cpus in the system. It will always show 0-100% regardless of how many cpus there are.

Return Values:

%1	cpu
%2	kernel
%3	processor queue length

CPUCOUNT

Shows the number of cpus in the system. This also reflects cores per cpu.

Return Values:

%1	cpu count
----	-----------

CPUTEMP

This item uses the standard WMI method for retrieving cpu temperature. If the hardware manufacturer has implemented it and you run Desktop Info as Administrator then it may work but more than likely it will not. I notice Win 10 1803 is able to show it.

Return Values:

%1	temperature
%2	critical threshold

CPUTYPE

Shows information about the brand and type of cpu.

Return Values:

%1	cpu information
----	-----------------

CPUUSAGE

Shows the usage for each cpu or core.

Available Options:

count	maximum number of cpus/cores to display
-------	---

Return Values:

%1	cpu usage
----	-----------

DATADUMP

Writes a csv data file for every active item. The data is the raw or formatted data from the most recent collection of each item. All csv files are written to the one directory. The file name consists of either the item lid or id and the date and time of the data collection.

Available Options:

dir	the directory to write the csv files
datatype	0=raw, 1=formatted

Return Values:

%1	the number of active items written
%2	date/time of last data dump

DATETIME

The current date and time of the host.

Return Values:

%1	day of week
%2	date
%3	month
%4	year

%5	hours
%6	minutes
%7	seconds

DIRECTX

Shows the Direct X version.

Return Values:

%1	Direct X version
----	------------------

DISPLAYCONTROLLER

Shows the current display controller information.

Return Values:

%1	display controller
----	--------------------

DNSSERVER

Shows all DNS servers over all network adapters.

Available Options:

multirow	0=comma delimited on a single line 1=one ip address per line
----------	---

Return Values:

%1	dns servers
----	-------------

DOMAIN

Shows the current domain.

Return Values:

%1	domain name
----	-------------

DOMAINCONTROLLER

Shows the current domain controller.

Return Values:

%1	domain controller
----	-------------------

ENVVAR

Shows the given environment variable. The variable must be set in the parent environment at the time the Desktop Info process was started.

Available Options:

key	the environment variable to return
-----	------------------------------------

Return Values:

%1	the value of the environment variable
----	---------------------------------------

EVENTLOG

Monitors event logs for changes.

Available Options:

log	name of the event log to monitor
-----	----------------------------------

Return Values:

%1	log name
----	----------

%2	last event log entry
----	----------------------

The following example will monitor the system event log:

```
EVENTLOG=active:1,interval:10,log:System,display:%2
```

FILE

Monitors files and folders for changes to size, write time or version number.

Available Options:

type	monitor type (text, size, time, version)
------	--

file	file or folder name
------	---------------------

Return Values:

%1	the file name being monitored
----	-------------------------------

%2	text: the first line of text in the file
----	--

	size: the file size
--	---------------------

	time: the last write and access times
--	---------------------------------------

	version: version number of the executable
--	---

This monitor will work for local and network files and folders. When monitoring a directory make sure there is no trailing backslash.

This example displays the contents of the given file whenever it changes:

```
FILE=active:1,interval:10,type:text,file:c:\temp\semaphore.txt
```

This example shows the executable version number whenever it changes:

```
FILE=active:1,interval:30,type:version,file:C:\desktopinfo\
desktopinfo.exe
```

FILE2TEXT

Displays the contents of the given text file containing 'key=value' pairs. The file may contain any number of lines of text. Any line that contains an equals '=' sign will be displayed; the text before the equals sign is displayed in the left column, the text after the equals sign is displayed in the right column. Set the interval if you want to update it at regular intervals. The display template is not used. User variables may be used in the text of the file.

Available Options:

file	name of file containing key=value pairs
------	---

Example:

```
FILE2TEXT=active:3,interval:3600,file:\assetinfo.txt
```

FILECONTENTS1

Displays the contents of the given text file in the right column. Set the interval if you want to update it at regular intervals. The display template is not used. User variables may be used in the text of the file.

Available Options:

file	name of file to display
------	-------------------------

Example:

```
FILECONTENTS1=active:1,interval:3600,text:Instructions,file:instructions.txt
```

FILECONTENTS2

Displays the given text file contents over both columns. Set the interval if you want to update it at regular intervals. The display template is not used. User variables may be used in the text of the file.

Available Options:

file	name of file to display
------	-------------------------

FILEEXIST

Checks if the given file exists and returns true or false. Use the boolean formatting to make a nice display.

Available Options:

file	file name to check
------	--------------------

Return Values:

%1	True or False
----	---------------

Example:

```
FILEEXIST=active:1,interval:10,file:\glennisawesome.txt,text:Is Glenn  
Awesome?,display:%1[b:Absolutely!:Not!]
```

This tests for the file "\glennisawesome.txt". If it exists the display will be:

```
"Is Glenn Awesome?           Absolutely!"
```

If the file doesn't exist, the display will be:

```
"Is Glenn Awesome?           Not!"
```

FIXEDDISK

Shows all fixed and mounted logical drives. It does not show optical, mapped or network drives. This is a parent item. It has one child, DISKIO.

Available Options:

count	maximum number of drives to show
filter	defines which drives will be displayed. case sensitive.

Return Values:

%1	drive
%2	volume
%3	used space
%4	free space
%5	total size
%6	size available
%7	percent used
%8	percent free

Example:

To show only drive C: add "filter:C:".

To show drives C: and E: add "filter:C: E:".

DISKIO

This is a child item of FIXEDDISK. It shows the disk activity of the parent fixed disk.

Return Values:

%1	reads per sec
----	---------------

%2	writes per sec
%3	queue size

HTTPGET

Makes a HTTP GET request to the given source url and displays whatever it returns. You can give it any url but it's really only useful for returning a short plain text message such as getting your public ip or if you have a http server that provides information. There is no default, if you don't specify a url, it will return an error.

Available Options:

source	url to send request
--------	---------------------

Return Values:

%1	returned value from http request
----	----------------------------------

Example:

```
HTTPGET=active:1,interval:600,source:http://plain-text-ip.com/
```

Here's a few other sites that return your public ip:

<https://ifconfig.co/ip>

<http://ipecho.net/plain>

<https://api.ipify.org/>

<https://wtfismyip.com/text>

<http://ident.me/>

<https://myexternalip.com/raw>

<http://plain-text-ip.com/>

HOST

Host name of the local machine.

Return Values:

%1	host name
----	-----------

IEVERSION

Shows the Internet Explorer version.

Return Values:

%1	ie version
----	------------

IF

Compares two values and if false, the following item is not displayed. If both values are valid numerical values, they are compared as numbers, if not they are compared as character strings. See [Conditional Visibility](#).

Available Options:

value1	the first value to compare	
value2	the second value to compare	
comparator	how to compare	
	eq	value1 and value2 are equal
	ne	value1 and value2 are not equal
	gt	value1 is greater than value2
	lt	value1 is less than value2
	ge	value1 is greater than or equal to value2
	le	value1 is less than or equal to value2
	contains	value1 contains value2
	notcontains	value1 does not contain value2

To perform a case sensitive comparison, prefix any of the comparators with 'c'. For example, 'eq' is case *insensitive* 'equals' and 'ceq' is case *sensitive* 'equals'.

LOADTIME

The time of day Desktop Info was loaded.

Return Values:

%1	day of week
%2	date
%3	month
%4	year
%5	hours
%6	minutes
%7	seconds

NETCONNECTIONS

Shows the current number of network connections.

Return Values:

%1	number of connections
----	-----------------------

NETPACKETS

Shows the total network ipv4 packs sent and received. Use the mtu option to convert packets to bytes.

Available Options:

mtu	multiply by this number to get bytes
-----	--------------------------------------

Return Values:

%1	packets (or bytes) received
----	-----------------------------

%2	packets (or bytes) sent
----	-------------------------

NETPACKETSRATE

Shows the current ipv4 send and receive rate of network packets. Use the mtu option to convert packets to bytes.

Available Options:

mtu	multiply by this number to get bytes
-----	--------------------------------------

Return Values:

%1	packets (or bytes) received / sec
----	-----------------------------------

%2	packets (or bytes) sent / sec
----	-------------------------------

NETWORKADAPTER

Shows all network adapters. This is a parent item. It's children are IPADDRESS, LEASEEXPIRY, GATEWAY, DHCPSEVER and WINSSERVER. Each of these child items takes a row on the display. You can display up to 8 adapters. This item is deprecated; you should use NETWORKINTERFACES instead.

Available Options:

activeonly	show only active network adapters
------------	-----------------------------------

filter	defines which adapters will be displayed
--------	--

count	maximum number of adapters to display
-------	---------------------------------------

Return Values:

%1	adapter name
----	--------------

The filter option may contain includes denoted by a '+' sign and excludes denoted by a '-' sign.

Example:

```
NETWORKADAPTER=active:1, interval:30, filter:+PCI+wireless-virtual
```


Shows all adapters that contain the keywords "PCI" and "wireless" and will exclude adapters that contain the keyword "virtual".

NETWORKADAPTER CHILD ITEMS

IPADDRESS

Shows the IP address of the parent network adapter.

Return Values:

%1	adapter ip
%2	subnet mask
%3	prefix length
%4	mac address

LEASEEXPIRY

Shows the lease expiry of the parent network adapter IP address.

Return Values:

%1	lease expiry
----	--------------

GATEWAY

Shows the gateway IP of the parent network adapter.

Return Values:

%1	gateway IP
----	------------

DHCPSEVER

Shows the dhcp server IP address of the parent network adapter.

Return Values:

%1	dhcp server
----	-------------

WINSSERVER

Shows the WINS server of the parent network adapter.

Return Values:

%1	wins server
----	-------------

NETWORKINTERFACES

Displays detailed information for the selected network interfaces. This supersedes the NETWORKADAPTER item.

Available Options:

operstatus	show only interfaces that have the specified operational status
iftype	show only interfaces that are the specified interface type
friendlyfilter	filter on the friendly name
descfilter	filter on the description

Return Values:

%1	adapter name
%2	friendly name
%3	description
%4	mac address
%5	mtu
%6	interface type
%7	operational status
%8	ipv4 address
%9	ipv4 mask
%10	ipv4 prefix length
%11	ipv6 address
%12	ipv6 mask (not implemented)
%13	ipv6 prefix length
%14	lease expiry
%15	ipv4 dns servers
%16	ipv6 dns servers
%17	ipv4 gateway *
%18	ipv6 gateway *
%19	pv4 dhcp server *
%20	ipv6 dhcp server *
%21	ipv4 wins server *
%22	ipv6 wins server *
%23	transmit link speed *
%24	receive link speed *

* These values are not available on Windows 2000 and XP.

The operstatus and iftype filters can contain multiple values separated by a space. For example, to show ethernet and wireless interfaces, "iftype:6 71". To show only active interfaces, "operstatus:1".

To see a full list of operational status and interface types go here:

https://docs.microsoft.com/en-us/windows/desktop/api/iptypes/ns-iptypes-_ip_adapter_addresses_lh

The friendlyfilter and descfilter options may contain includes denoted by a '+' sign and excludes denoted by a '-' sign.

Example:

```
friendlyfilter:+wireless-virtual
```

Shows all interfaces that contain the keyword "wireless" and will exclude interfaces that contain the keyword "virtual".

If there is more than one filter match, they are evaluated left to right and the last one wins. For example, "friendlyfilter:+wireless-wire" will include all interfaces with "wireless" in the friendly name and then exclude any interface with "wire" in the friendly name, resulting in no wireless interfaces.

An interface must match all the given filters in order to be displayed.

OEMINFO

Attempts to read the OEM Information set in either the OEMInfo.ini file or the OEMInformation registry key in either the 64 bit or 32 bit branch of the registry.

Return Values:

%1	manufacturer
%2	model
%3	Support Provider
%4	Support URL
%5	Support Hours
%6	Support Phone

OSBUILD

Shows the Windows operating system version and build number.

Return Values:

%1	build number
----	--------------

PAGEFAULTS

Shows both total and hard page faults (reads and writes). The hard page faults is usually the one you're interested in. This shows page file activity which is what can potentially kill system performance. Maybe even worth putting a threshold on the second value. The hard page faults are further broken down into 'pages read from disk per second' and 'pages written to disk per second'.

Return Values:

%1	total faults per second
%2	hard page faults per second
%3	pages read from disk per second
%4	pages written to disk per second

PAGEFILE

Shows Windows page file usage.

Return Values:

%1	page file used
%2	total page file size
%3	percent page file used
%4	page file free
%5	percent page file free

PHYSICALRAM

Shows physical memory usage.

Return Values:

%1	used ram
%2	total ram
%3	percent used ram
%4	free ram
%5	percent free ram

PROCESSCOUNT

Total number of Windows processes.

Return Values:

%1	number of processes
----	---------------------

PROCESSMEM

Shows memory and cpu usage for the given process. If there is more than one instance of the given process name, they are all included in the total.

Available Options:

key	name of the process to monitor
-----	--------------------------------

Return Values:

%1	working set size
%2	page file usage
%3	page fault count
%4	cpu usage
%5	private usage (commit size etc)

PROXY

Shows network proxy server and enabled status.

Return Values:

%1	proxy server
%2	enabled state

RDSSESSIONID

Shows the Remote Desktop Services session id associated with the current process.

Return Values:

%1	process id
%2	session id

REG

Shows the given value from the registry. Not to be confused with the REGISTRY monitor item, this item just retrieves the given value at a regular interval. It can only show integers and strings.

Available Options:

value	the registry key and value name to be read
wow	32=read from the 32 bit registry 64=read from the 64 bit registry
host	optional remote host

Return Values:

%1 the value retrieved from the registry

The value option should contain the root key as well as the key and value name:

```
value:HKEY_LOCAL_MACHINE\SOFTWARE\TeamViewer\Version5\ClientID
```

To access the registry on a remote host, set the host option to the host name of the remote computer. Both computers must have the Remote Registry service running. The Desktop Info user obviously must have permissions on the remote host. Remote registry access may be restricted by domain or local policy. For more information on a possible solution, go to:

<https://support.microsoft.com/en-au/help/951016/description-of-user-account-control-and-remote-restrictions-in-windows>

For more information on the wow option, go to:

<https://docs.microsoft.com/en-us/windows/desktop/winprog64/accessing-an-alternate-registry-view>

REGEXIST

Shows whether the given registry key or value exists. Use the boolean formatting to show a meaningful display.

Available Options:

value	the registry key or key\value to be tested
wow	32=read from the 32 bit registry 64=read from the 64 bit registry
host	optional remote host

Return Values:

%1 true or false if the key or key\value exists

The value option should contain the root key as well as the key and optional value name:

```
value:HKEY_LOCAL_MACHINE\SOFTWARE\TeamViewer\Version5\
ClientID,display:%1[b:Yes:No]
```

To access the registry on a remote host, set the host option to the host name of the remote computer. Both computers must have the Remote Registry service running. The Desktop Info user obviously must have permissions on the remote host. Remote registry access may be restricted by domain or local policy. For more information on a possible solution, go to:

<https://support.microsoft.com/en-au/help/951016/description-of-user-account-control-and-remote-restrictions-in-windows>

REGISTRY

Monitors registry keys or values for changes.

Available Options:

tree	0 to monitor the key
	1 to monitor the tree starting at key
key	the key or key\value to monitor

Return Values:

%1	required value
%2	date/time of change

If you specify a key, %1 is not used. You can also choose to monitor just that key or the entire tree starting at that key.

The following example will monitor a value in the Run key.

```
REGISTRY=active:1,tree:0,text:Run Key Test,key:HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Run\Test
```

If the registry key contains a comma, precede it with a backslash.

Invalid Key

```
HKEY_LOCAL_MACHINE\SOFTWARE\Apple Computer, Inc.
```

Valid Key

```
HKEY_LOCAL_MACHINE\SOFTWARE\Apple Computer\, Inc.
```

SERVICEPACK

Shows the Windows service pack edition.

Return Values:

%1	service pack
----	--------------

SESSIONID

Shows the active console session id.

Return Values:

%1	session id
----	------------

SET

Sets the value for the given user variable. See the section on [User Variables](#).

Available Options:

key	the user variable you want to set
value	the value to place in the user variable

TEXT

Displays any fixed key/value text. Useful for any kind of internal identification or other static information such as a machine's context, use, operator, tech support info. It can also be used to display a number of user variables on one line.

Available Options:

text	Text to display in the left column
display	Text to display in the right column

TIMEZONE

Current Windows time zone.

Return Values:

%1	time zone
----	-----------

TOPPROCESSCPU

Shows the process with the highest cpu usage. Desktop Info can only show processes it has permissions to read. Running as administrator or a member of the administrators group is enough for most processes but not for some system processes. Desktop Info will attempt to enable privileges to read system process information.

Return Values:

%1	process name
%2	process id
%3	percent

TOPPROCESSMEM

Shows the process with the highest memory usage. The memory counter used can be either the "Working Set Size" or "Page File / Private Usage" (Microsoft sometimes refers to the latter as "Commit Charge" or "Commit Size"). If desktopinfo64.exe is running, 'pu' will return Private Usage, otherwise it will return Page File Usage. In theory they are the same value., however Microsoft states that on Windows 7 and earlier, Page File Usage is always 0. If desktopinfo64.exe is not running, Private Usage is not available and Page File Usage is returned.

Available Options:

counter	which memory counter to use
	ws = Working Set Size
	pu = Page File Usage (32 bit mode)
	or Private Usage (64 bit mode)

Return Values:

%1	process name
%2	process id
%3	usage bytes

TOPPROCESSPF

Shows the process with the highest page faults. This is not page faults per second, it's the total page faults since the last collection.

Return Values:

%1	process name
%2	process id
%3	page faults

TSSESSIONS

Shows the number of terminal sessions.

Return Values:

%1	number of sessions
----	--------------------

UNREADMAIL

Show the number of unread mails.

Return Values:

%1	number of unread mails
----	------------------------

UPTIME

Total time Windows has been running.

Return Values:

%1	days
%2	hours
%3	minutes
%4	seconds

USER

Current Windows user account name.

Return Values:

%1 user name

VIRTUALMEMORY

Shows Windows virtual memory usage.

Return Values:

%1	used memory
%2	total memory
%3	percent used memory
%4	free memory
%5	percent free memory

WMI

Executes a custom WMI query. Because there is an implied "select * from ", all properties are returned so you can include as many properties as you like in the display output.

Available Options:

namespace	WMI namespace such as 'root\wmi' or 'root\cimv2'
query	the wmi class and optional where clause but NOT the select clause (this is implied)
maxrows	the maximum number of rows to display There will always be at least one row so 0 and 1 are effectively the same thing.

Return Values:

Returned values are indicated by enclosing a wmi property name in % signs.
eg a bios property, SerialNumber, is indicated as %SerialNumber%. This is replaced in the display template by the actual value returned by the wmi query.
Additionally, the %rowcount% property will display the number of rows in the WMI result set. See below for an example.

Example:

```
WMI=active:1,namespace:root\cimv2,query:Win32_Bios,display:
%SerialNumber%
```

WMI Where Clause

This one displays multiple values from the wmi query with added text. Notice that the *where* clause contains a literal string in double quotes. Notice also how the *where* clause may include the 'like' keyword with wildcards.

```
WMI=active:1,namespace:root\  
cimv2,query:Win32_PerfFormattedData_Tcpip_NetworkInterface where Name  
like "%Wireless%",display:Rcvd: %BytesReceivedPersec% Sent:  
%BytesSentPersec% bytes per sec
```

You can add the NOT key to exclude rows from the result. It goes before the property in question thus:

```
query:Win32_PerfFormattedData_Tcpip_NetworkInterface where not Name  
like "%Wireless%"
```

In this example, WMI doesn't have a single query that returns the screen resolution and color depth so we run two queries and combine the output. The first query returns the color depth and stores it in a user variable (see below). The second query returns the resolution and displays it along with the previous user variable.

```
WMI=active:2,namespace:root\  
cimv2,query:Win32_DisplayConfiguration,set:BitsPerPel,display:  
%BitsPerPel%  
  
WMI=active:1,namespace:root\cimv2,query:Win32_DesktopMonitor,display:  
%ScreenWidth%x%ScreenHeight%x%BitsPerPel%
```

You can also append the number formatting as described earlier. You should make sure the selected format matches the type of value you are trying to format.

WMI Row Count

The *maxrows* option will display at most the given number of rows. If you set *maxrows* to 1 and set the *display* option to %rowcount%, you can show just the number of rows without displaying all the rows. This is useful, for example, for displaying the number of Windows updates available without showing all the updates.

```
WMI=active:1,interval:60,text:Windows Updates,namespace:root\  
cimv2,query:win32_quickfixengineering,maxrows:1,display:%rowcount%  
updates available
```

WMI Date/Time Formatting

If a CIM_DATETIME field is detected, it is automatically split into its component parts and added to the result set. These new date/time component properties are named starting with the original property name, followed by an underscore, followed by the date/time component.

```
_year, _month, _day, _hour, _minute, _second, _msecond, _utcoffset
```

See the Microsoft page for more information:

<https://docs.microsoft.com/en-us/windows/desktop/wmisdk/cim-datetime>

These components are available in the [display template](#) with date/time formatting so you can create a more user friendly display.

For example, the Win32_OperatingSystem query contains a property called %InstallDate%. This property is displayed as “20181217091440.000000+120”. It’s readable, kind of. It is a CIM_DATETIME type and so it will be automatically split into it’s component parts with the result that, along with the %installdate% property there is also %installdate_year%, %installdate_month%, %installdate_day% etc. These new properties are available to the display template and may be formatted to your taste. For example:

```
text:Windows Install Date, display:%installdate_day%  
%installdate_month%[mmm] %installdate_year%
```

The CIM_DATETIME field has a very specific format. Not all WMI date/time fields are of this type. Only this type will be split.

WMI Explorer is an easy tool to explore the WMI system. <http://www.ks-soft.net/>

Useful WMI Queries

Here are some useful WMI queries that you can plug straight into the desktopinfo.ini file. Note, these are all supposed to be a single line. You can't split lines in the ini file.

Windows Workgroup

```
WMI=active:1,text:Workgroup,namespace:root\  
cimv2,query:Win32_ComputerSystem,display:%Domain%
```

Default Printer

```
WMI=active:1,text:Default Printer, namespace:root\  
cimv2,query:Win32_Printer where default = "True",display:%Name%  
(%Status%)
```

All Printers

```
WMI=active:1,text:Printers,namespace:root\  
cimv2,query:Win32_Printer,display:%Name% (%Status%)
```

Windows Update Service

```
WMI=active:1,interval:60,text:Windows Upd Service, namespace:root\  
cimv2, query:Win32_Service where name="wuauserv",display:%state%\  
,%status%
```

Lanman Service

```
WMI=active:1,interval:60,text:Lanman Service, namespace:root\  
cimv2, query:Win32_Service where name="lanmanserver",display:%state%\  
,%status%
```

Windows Firewall

```
WMI=active:1,interval:60,text:Windows Firewall, namespace:root\  
cimv2, query:Win32_Service where name="mpssvc",display:%state%\  
,%status%
```

Anti Malware Service

```
WMI=active:1,interval:60,text:Anti Malware Service, namespace:root\  
cimv2, query:Win32_Service where name="MsMpSvc",display:%state%\  
,%status%
```

Video Controller

```
WMI=active:1,text:Video Controller, namespace:root\  
cimv2, query:Win32_VideoController,display:%Caption%
```

Ethernet Nic Speed

```
WMI=active:1,interval:5,text:Ethernet Speed, namespace:root\  
cimv2, query:Win32_NetworkAdapter where Name like "%PCI-E%",display:%Speed  
%[1.0B]Bps
```

Wifi Speed

```
WMI=active:1,interval:5,text:Wifi Speed, namespace:root\cimv2,  
query:Win32_NetworkAdapter where Name like "%wireless%",display:%Speed  
%[1.0B]Bps
```

Network Latency

```
WMI=active:1,interval:60,text:Network Latency, namespace:root\cimv2,  
query:Win32_PingStatus where address='google.com',display:  
%ResponseTime%ms (google.com)
```

Logical Disks

```
WMI=active:1,interval:10,text:Logical Disks, namespace:root\cimv2,  
query:Win32_PerfFormattedData_PerfDisk_LogicalDisk where Name !=  
"_Total",display:%name% r:%DiskReadBytesPersec%[3.1k]KiBps\, w:  
%DiskWriteBytesPersec%[3.1k]KiBps
```

Batteries

```
WMI=active:1,interval:60,text:Batteries,namespace:root\  
cimv2,query:Win32_Battery,display:%Description%: r:  
%EstimatedChargeRemaining%%
```

Asset Tag

```
WMI=active:1,text:Asset Tag, namespace:root\cimv2,  
query:Win32_SystemEnclosure,display:%SMBIOSAssetTag%
```

Server Sessions

```
WMI=active:1,interval:60,text:Server Sessions, namespace:root\cimv2,  
query:Win32_PerfFormattedData_PerfNet_Server,display:Sessions:  
%ServerSessions%\, Files: %FilesOpen%
```

Tcpv4 Connections

```
WMI=active:1,interval:10,text:Tcpv4 Connections, namespace:root\cimv2,  
query:Win32_PerfFormattedData_Tcpip_TCPv4,display:  
%ConnectionsEstablished%
```

Tcpv6 Connections

```
WMI=active:1,interval:10,text:Tcpv6 Connections, namespace:root\cimv2,  
query:Win32_PerfFormattedData_Tcpip_TCPv6, display:  
%ConnectionsEstablished%
```

Shared Resources

```
WMI=active:1,interval:60,text:Shared Resources, namespace:root\cimv2,  
query:Win32_Share where not Name like "%$%",display:%Name% [%Status%]
```

Anti Virus Product

```
WMI=active:1,interval:60,text:Anti-Virus,namespace:root\
SecurityCenter2,query:AntiVirusProduct,display:%displayName%
%productState%[bit:4096:Enabled:Disabled] and %productState%
[bit:393216:up to date:not up to date]
```

Physical Disk Status

```
WMI=active:1,interval:60,text:Physical Disks,namespace:root\
cimv2,query:Win32_DiskDrive,display:%Caption%| DeviceID: %DeviceID%|
Model:%Model%| Status:%Status%
```

Available Windows Updates

```
WMI=active:1,interval:60,text:Windows Updates,namespace:root\
cimv2,query:win32_quickfixengineering,display:%HotfixId%
```

Number of Available Windows Updates

```
WMI=active:1,interval:60,text:Windows Updates,namespace:root\
cimv2,query:win32_quickfixengineering,maxrows:1,display:%rowcount%
updates available
```

References

WMI Explorer

<http://www.ks-soft.net/>

Core Temp

<http://www.alcpu.com/CoreTemp/>

Understanding Kilobytes

<https://en.wikipedia.org/wiki/Kilobyte>

Network Interfaces Reference

https://docs.microsoft.com/en-us/windows/desktop/api/iptypes/ns-iptypes-_ip_adapter_addresses_lh

The Registry Wow View

<https://docs.microsoft.com/en-us/windows/desktop/winprog64/accessing-an-alternate-registry-view>

The Windows Virtual Screen

<https://docs.microsoft.com/en-us/windows/desktop/gdi/the-virtual-screen>

Release Notes

Version v0.1.0

2005

Limited distribution test release.

Version v0.1.1

2005

Change 1: Fixed the nasty flicker some systems were getting.

Change 2: Fixed the odd characters after the domain name.

Change 3: Less full refreshes means less cpu time.

Change 4: Fixed disk figures for very small drives.

Version v0.2.0

2005

Change 1: Added time zone info.

Change 2: Some optimisations.

Change 3: Added refresh intervals.

Change 4: Added domain controller info.

Change 5: Added event logs.

Version v0.2.1

December 2005

Change 1: Added terminal server session count.

Change 2: Fixed some stuff in event logs.

Version v0.2.2

December 2005

Change 1: Added DirectX version.

Change 2: Adjusted domain controller. I can't directly test this one.

Change 3: Added network packet stats and rates.

Change 4: Added network connection count.

Change 5: Added double click refresh.

Version v0.3.0

Change 1: Fixed a bunch of memory issues.

Change 2: Fixed Terminal Services sessions and added session list.

Change 3: Added auto font size.

Change 4: Added 'missing ini' default values.

Change 5: Implemented proper ini file monitoring.

Change 6: Added screen info.

Change 7: Fixed display for 256 color remote desktop.

Change 8: Added files monitor options.

Version v0.3.1

June 2006

Change 1: Added Up Time.

Change 2: Added support for cpu times for Windows 2000.

Change 3: Fixed Domain Controller

Change 4: Fixed multiples of same file watch type bug.

Change 5: Fixed memory sizes over 2GB.

Version v0.4.0

July 2006

Change 1: Added top process cpu time.

Change 2: Added top process memory usage.

Change 3: Added file version watch type.

Change 4: Added registry watch types.

Change 5: Added cpu count.

Change 6: Additional checking for terminal sessions.

Version v0.4.1

December 2006

Change 1: Added unread mail.

Change 2: Added formright and formbottom options.

Version v0.4.2

October 2007

Change 1: Increased fixed disks to eight.

Change 2: Added multiple ip addresses.

Change 3: Fixed problem with missing ini file.

Change 4: Split network gateway entries to separate lines.

Change 5: Added percentages to memory and disk displays.

Version v0.5.0

July 2008

Change 1: I think I've nailed the show desktop thing.

Version v0.5.1

Change 1: Fixed problem with some USB drives.

Change 2: Solved refresh problem when removable drives come and go.

Version v0.6.0

November 2008

Change 1: Reworked the file monitoring so it works on local and remote files and folders. You'll need to adjust your ini file entries as noted above.

Change 2: Reworked the registry monitoring to merge the two types. You'll need to adjust your ini file entries as noted above.

Change 3: Added the /f command line option to show a visible, moveable form.

Change 4: Added the /a command line option to show all items regardless of the ini file settings.

Change 5: Added right click context menu.

Change 6: The network entries are grouped so all information for each adapter is together.

Change 7: Tested on a variety of Windows platforms. The results are noted above.

Version v0.7.0

January 2009

Change 1: Added Disk IO on fixed logical drives.

Change 2: Added disk queue length.

Change 3: Changed ini file format as noted above. Will continue to read the old format while the Intervals section exists.

Change 4: Added item colors.

Change 5: Fixed bug in Top Process Cpu

Change 6: Fixed bug in cpu times.

Change 7: Added charts.

Change 8: Added thresholds.

Change 9: Added exception handlers to process enumerators.

Version v0.7.1

Change 1: Fixed an access violation in the disk io routines.

Change 2: Fixed refresh when disks come and go.

Version v0.8.0

Change 1: Added colors to the file and registry monitors.

Change 2: Added option to disable the context menu.

Change 3: Added option to toggle the indents on disks/networks.

Change 4: Modified registry monitor to optionally show values.

Change 5: Registry item names are shown as found in the ini file.

Change 6: Added event log monitor and removed redundant event logs from the items.

Version v0.8.1

Change 1: Improved disk change handling.

Change 2: Fixed file monitor where file/directory does not exist or disappears or reappears.

Change 3: Fixed divide by zero error in fixed disks.

Version v0.9.0

Change 1: Refactored the chart display code to be more useful and added charts to more items. See the charts section for more information.

Change 2: Refactored form display code. Options have changed accordingly. Auto form width, auto font size and font color are gone. You should make sure every item has the color set. See the options section for more information.

Change 3: Rewritten all the network adapter stuff. Added change handling. Added filtering. See the options section for more information.

Change 4: Prevent form from resetting it's position after it is dragged.

Change 5: Rewrote the bar chart.

Change 6: Fixed problem with event log monitor thread not terminating correctly.

Change 7: Added the following items: printer, printerstatus, displaycontroller, bios, motherboard, workgroup. Printers is work in progress.

Change 8: Added language file.

Change 9: Added screen saver option.

Change 10: Added msnstatus option.

Change 11: Changed method for retrieving service pack.

Version v1.0.0

Change 1: Added page faults and top process page faults.

Change 2: The order of displayed items now follows the order in the ini file.

Change 3: New ini file item format. This will make it easier to read and easier for me to add new options. See the item section above for more details.

Change 4: Fixed the process name for all known varieties of Windows. If a process name can't be retrieved for any reason, it will display <n/a> and maybe an error message.

Change 5: Added cpu temperature from wmi. See the miscellaneous section above.

Change 6: Fixed line chart width in screen saver mode.

Change 7: Subdued some redundant refreshes.

Change 8: Some memory usage optimisations.

Change 9: Fixed display controller and bios on Windows 7 and hopefully haven't broken it elsewhere.

Change 10: Added oeminfo. See miscellaneous section above.

Change 11: Added item font style.

Version v1.0.1

June 2010

Change 1: Fixed fatal crash on startup as the result of an access denied problem when retrieving OS info in limited access Windows account.

Version v1.1.0

January 2011

Change 1: Added battery status.

Change 2: Added option to disable ClearType.

Change 3: Added header item. See ini file.

Change 4: Added cpu kernel time.

Change 5: Added inimonitortime to options. This is the number of seconds to check the desktopinfo.ini file for changes.

Change 6: Added osbuild.

Change 7: Fixed a problem with reading process information for some system processes.

Change 8: Removed DISKQUEUE item. It's included on the DISKIO item.

Change 9: Added filter option to FIXEDDISK item.

Version v1.1.1

Change 1: Changed the way the Windows architecture is determined.

Change 2: Fixed the transparency on 16 bit color display.

Version v1.1.2

Change 1: Forgot to switch off debug causing large log file, oops.

Version v1.2.0

October 2013

Change 1: Fixed index out of bounds when battery chart type is 2.

Change 2: Added network PROXY item.

Change 3: Changed HEADER item into more general COMMENT item.

Change 4: COMMENT is ignored when calculating width of column 1 allowing it to display over both columns.

Change 5: Added underline to style option.

Change 6: Changed FORMCOLOR in the main options section to a bgr type value to keep it consistent with other colors. 000000 means transparent in normal mode or black background in form mode.

Change 7: Converted file monitor into a regular item. Now you can put one or more file monitor items anywhere in the items list.

Change 8: Converted registry monitor into a regular item. Now you can put one or more registry monitor items anywhere in the items list.

Change 9: Fixed problem with monitoring registry on 64 bit Windows.

Change 10: Converted event log monitor into a regular item. Now you can put one or more event log monitor items anywhere in the items list.

Change 11: Added AUDIOCONTROLLER item.

Change 12: Added logging option.

Change 13: Added /ini command line option.

Change 14: Added SERIALNUMBER item.

Change 15: Added multiple IP addresses per nic.

Change 16: Added option to allow/disallow dragging the form.

Change 17: Added offset property to network items.

Change 18: Added multi core cpu item, CPUUSAGE.

Change 19: Added activeonly property to NETWORKADAPTER.

Change 20: Added count property to control maximum number of multi items displayed (CPUUSAGE, NETWORKADAPTER, FIXEDDISK, PRINTER).

Version v1.3.0

January 2014

Change 1: Fixed critical error where USB drive is ejected but not removed.

Change 2: Added SHORTDISPLAY option to PHYSICALRAM, VIRTUALMEMORY, PAGEFILE and FIXEDDISK items.

Change 3: Added ENVVAR item.

Change 4: Added DEFAULTPRINTER item.

Change 5: Added SHORTDISPLAY option to the registry monitor.

Change 6: Added LOGONSESSION item.

Change 7: Moved network adapter filter to the item configuration and is much more flexible with include and exclude options.

Version v1.4.0

February 2014

Change 1: Added ALLIPADDRESS. This is a stand alone item to display all active IP addresses without depending on the NETWORKADAPTER item.

Change 2: Fixed critical error where a network adapter has more than one ip address sometimes causes an access violation.

Change 3: Improved response for changing network adapters, fixed disks and screen resolution.

Change 4: Added hidden items. Set active to 2. Right click and select Show Hidden Items. See above.

Change 5: Added OEMPRODUCT item. See above.

Change 6: Added SUBNETMASK item.

Change 7: Added csv option to items. See above.

Change 8: Fixed disk filter got lost during last version.

Change 9: Apparently fixed an obscure wmi bug.

Change 10: Fixed CPUTEMP charts.

Change 11: Added SERVICESTATE.

Change 12: Added TEXT.

Change 13: Added hook to Core Temp temperature reader.

Change 14: Added custom WMI item. See above for details. There's some examples in the ini file. These may duplicate existing items. I'll leave the old items in for this release and if all goes well they'll be removed next release.

Change 15: Adjusted screen saver display.

Version v1.5.0

March 2014

Change 1: Fixed wmi line chart resetting when switching between hidden and not hidden.

Change 2: Added volume to FIXEDDISK.

Change 3: There was a test item called PROCESSMEM which was hard wired to DesktopInfo.exe. I've modified this so you can point it to any process name. The result will be the sum of all processes by that name. 'ws' is Working Set, 'pf' is Page File Usage or Commit Size.

Change 4: Added 'column1width' to global options.

Change 5: Added format option to WMI item.

Change 6: Added centerv and centerh to options.

Change 7: Removed following items as they can now be done with WMI: SERVICESTATE, AUDIOCONTROLLER, SERIALNUMBER, WORKGROUP. The ini file has been updated as appropriate.

Change 8: I don't know what I was thinking with LOGONSESSION.

Change 9: Added a global exception handler so maybe we won't see any more of those cascading error messages.

Change 10: Added option to adjust background transparency.

Change 11: Cleaned up the display code and fixed a few little annoyances.

Change 12: Fixed IEVERSION to include svcversion updates.

Version v1.5.1

April 2014

Change 1: Fixed charts updating every second even though data is not updated.

Change 2: Fixed regression bug with COMMENT item.

Change 3: Fixed refresh ugliness and missing top lines.

Version v1.6.0

August 2014

Change 1: Major refactor of the internal procedure calls.

Change 2: Reduced the display flickering some more.

Version v1.7.0

August 2018

(Four years, that's not so bad is it?)

There's been a regular stream of inquiries over the years about Desktop Info to warrant looking into resurrecting it. The last official release was v1.5.1 in April 2014. I made available an unofficial version 1.6.0 in November 2017 which was a compile I did in August 2014 and never released. I was amazed to see it working on Windows 10. However some people are having issues so I'm going to make an attempt at resolving those and see where that takes us.

Change 1: Signing with digital code certificate. You can confirm this by right clicking the DesktopInfo.exe, select Properties and the Digital Signatures tab.

Change 2: Removed secondary form from Windows task switcher.

Change 3: Removed MSN status option.

Change 4: Now correctly reads unicode language files. The language files must be UTF-8 encoded.

Change 5: The language files are now collected in the "language" sub-directory. Make sure you specify the sub-directory in the desktopinfo.ini file entry. Send me your language files to be included in future releases.

Change 6: Doubled the size of item text so you can have longer comments.

Change 7: FIXEDDISK now correctly reads *only* local fixed and removable drives, not remote, network, mapped or optical drives. No longer constantly polls drives when the FIXEDDISK item is not active.

Change 8: UPTIME is no longer capped at 49 days.

Change 9: Added ShortDisplay to UPTIME.

Change 10: Added UTCTIME. This seems to take a while to run so maybe set a higher interval.

Change 11: Added full width underline style.

Change 12: I made a mistake with the TEXT item. The last field should be 'display' and not 'key'. You should change your ini file to match.

Change 13: Added user variables. See the section above for details.

Change 14: Added csvdatatype option to items. Data logging no longer outputs the data in it's display form by default. The default value of 0 outputs the data in it's raw format. A value of 1 will output the data in the format it is displayed. See data logging section above for more information.

Version v1.8.0

September 2018

This version represents another not insignificant refactor which allows us to do a whole bunch of stuff we couldn't do previously. You should review the readme.txt, there's lots of new information there. There may be things I've broken that I haven't discovered yet. Your current ini file will need modifications to bring it up to speed but it might be simpler to just start again with the new one. Let me know if something breaks that hasn't been mentioned here.

Change 1: The first upshot of the big refactor is the addition of the 'display' template property to every item. This allows you to control how the data is displayed. See the items section above for details. This also means the 'shortdisplay' property is gone; you set your own display.

Change 2: The second upshot of the big refactor is that many items now offer multiple values for display. You decide which values you want by using replaceable parameters in the display template. Not all items have fully implemented this yet, more to come in future releases.

Change 3: The third upshot of the big refactor is a whole new formatting system included with the display template. You now have much more control over numbers, dates, times, bytes, speeds and booleans. See the Formatting sections above for much information.

Change 4: The custom WMI item has also undergone a major renovation and is much more useful now. The 'property' and 'format' options are gone and replaced with the 'display' template option. As with the other items, the WMI display template option allows you to specify the complete text you want to display including any and all returned wmi property values and formatting. See the Custom WMI section for details.

Change 5: The WMI item can now display multiple rows. If your wmi query returns more than one row, additional rows will be added to the display.

Change 6: Added HTTPGET item. This item will make a simple HTTP GET request to the given source url and display whatever it returns. Useful for displaying your public ip for example. See the Http Get section for more information.

Change 7: Removed SCREEN and OSVERSION items. They are returning innaccurate information so we'll use the WMI call instead. See the ini file for the replacements.

Change 8: Removed BIOS, OEMPRODUCT, MOTHERBOARD, PRINTER, PRINTERSTATUS, DEFAULTPRINTER, UTCTIME items. These are all wrappers for WMI calls so now we'll just use WMI directly with some nice formatting. See the ini file for the replacements.

Change 9: Fixed problem reading registry key with a comma in the name. A comma in a registry key should be preceded by a backslash. See above for more information.

Change 10: Added FILEEXIST item. Displays whether the given file exists. See the section above for details and the ini file for an example.

Change 11: Fixed column 1 auto width calculation.

Change 12: Added LOADTIME which is the time of day that Desktop Info was executed.

Change 13: Changed process priority from 'idle' to 'below normal'. I don't expect this to have any impact other than the display refreshes are a little smoother.

Change 14: Speaking of display refreshes, I've hopefully streamlined it some more to reduce unnecessary redraws.

Change 15: If an item color is not defined it will take on the color of the previous item. In this way you set the color of the first item in a block and all successive items will be the same.

Change 16: ALLIPADDRESS now puts one entry per line so if you have multiple IP addresses, there will be multiple lines. Might have found the bug where it crashes when a network interface goes away.

Change 17: Added FILECONTENTS1 and FILECONTENTS2 for displaying the contents of a text file.

Change 18: Removed SUBNETMASK and MACADDRESS sub-items and added them as a second and fourth value (%2 and %4) to IPADDRESS.

Change 19: Added prefix as a third value to IPADDRESS.

Change 20: Added subnet mask and prefix as second and third values to ALLIPADDRESS.

Change 21: Now correctly resets it's position when the desktop size changes (maybe).

Change 22: Added 'noresults' option to the language files which is displayed when a query returns no rows, eg WMI.

Change 23: More improvement in language support. All 'text' has been moved out of the desktopinfo.ini file and into the language files. Each key in the language file is either an item id or a language id (lid) in the desktopinfo.ini file. See the section above for more information. Consider the 'text' option in the desktopinfo.ini file deprecated.

Version v1.9.0

October 2018

My primary objective in this release is to rework the raw data infrastructure so that I can store and move all the collected data and have better control over what data is displayed, charted and logged to csv. For now chart data remains pre-selected and the WMI item charts the first two numbers returned. In the next release I will open this up so you can select which values you want to chart. I'm also adding lots of information to the readme file.

Change 1: Reworked the internal data infrastructure for better control.

Change 2: All items now have the potential to be multi line.

Change 3: Implemented line breaks in the display template. Place a pipe symbol, '|' to indicate where you want a line break.

Change 4: Added NETWORKINTERFACES item. This is the alternative to the NETWORKADAPTER item and it's sub-items. It has much more information and display control. Read the item reference for more info. NETWORKADAPTER is deprecated.

Change 5: Reworked the internal item options infrastructure to make it much simpler to add new options to items and pass them on to the procedures.

Change 6: Added 'multirow' option to ALLIPADDRESS, DNSSERVER. This gives you the option of displaying the data over multiple rows instead of all on a single row.

Change 7: Much work on the csv logging. It is now logging all collected data, raw or formatted. Any items that return multiple rows will have all rows written.

Change 8: Added the item reference to the readme file. It should be complete by now. Let me know if something is missing.

Change 9: Removed 'offset' option in the global section of the ini. Added it as an option to the CPUUSAGE, NETWORKADAPTER and FIXEDDISK sub-items.

Change 10: Added DATADUMP item. When this fires it writes a csv file for every active item.

Change 11: Completed implementation of language 'noresults' option.

Change 12: Added the REG item which displays a value from the registry.

Change 13: Added language file change notifier.

Change 14: Added cpu and page faults to PROCESSMEM. Maybe it should be PROCESSMON?

Change 15: Updated the debug logging for all items and display data.

Change 16: Added 'logo' png graphic header to the language file. I know you don't like my silly logo. You put your own logo in.

Change 17: Font config has been moved out of the desktopinfo.ini file to the language files. This is so you can set a font for a specific language.

Change 18: Added font-charset to font config in language files. I'm still learning how to do languages so this might take a couple of iterations.

Change 19: Added language config to the context menu.

Version v1.9.1

October 2018

Change 1: Resolved some Unicode issues. Debug log is now unicode.

Change 2: Fixed issue with not resetting it's position after display size change.

Version v1.9.2

October 2018

Change 1: Fixed some fatal issues with the FILE/REGISTRY/EVENT monitor items.

Change 2: Fixed formcolor bug.

Version v1.10.0

November 2018

Important changes from v1.8.0 and v1.9.0: In those versions I started moving config options out of the main ini file and into separate language files. I'm not happy with the way that's working out so I've returned to making the desktopinfo.ini file the primary configuration file and the language files will simply override that if required. In most cases you will not need a language file at all. My apologies if I made work for you.

In this release we continue to reap the benefits of the raw data infrastructure refactor done in v1.9.0 with major improvements in both the charting and threshold functions. I've also been working hard on language support so we can now display non Latin based languages.

Change 1: Revamped the thresholds so we can have up to 3 thresholds on each item using any returned value *plus* we can have negative thresholds *plus* we can have thresholds on WMI items. See the [Thresholds](#) section for more info.

Change 2: Revamped the charts so we can chart any numerical value from any item including WMI items, bar or line, linear or logarithmic, colors, thresholds etc. See the [Charts](#) section for details.

Change 3: Added [REGEXIST](#) item.

Change 4: ALLIPADDRESS has been extracted from its dependency on NETWORKADAPTER, its list and its 'activeonly' and 'filter' options. It will now work independently. NETWORKADAPTER is deprecated.

Change 5: I've taken the 'hidden' page of items and turned it into a whole series of pages. Previously, "active:2" was the special 'hidden' page. This is now simply page 2 out of 9 pages. See the [Pages](#) section for more info.

Change 6: The readme.txt file was getting too big. Time for a proper manual.

Change 7: Added [FILE2TEXT](#) item.

Change 8: [OEMINFO](#) now checks both 64 bit and 32 bit branches of the registry tree.

Change 9: Added [log-level option](#).

Change 10: Splitting the config between two files was a bad idea so I thought it out again and the desktopinfo.ini file returns to being the primary configuration file. Everything is configured within that file. If you wish to override any options or text without altering the main configuration, create a language file. See the [Language File](#) section for more information.

Change 11: Much work on unicode support means we can now create and display non Latin languages such as Croatian, Chinese, Japanese etc via the language files. There is still work to be done to make the main ini file fully unicode so for now you must use the language files for multi-byte text.

Change 12: Added right-to-left support for Arabic languages. It's not complete but it is usable. If you find any errors in any of my sample language files please let me know.

Change 13: More work reducing the flicker/shimmer.

Change 14: The package no longer contains the desktopinfo.ini file, the file is renamed to desktopinfo-sample.ini. This is in order to prevent accidentally overwriting your finely tuned custom config file when the new version arrives. When Desktop Info runs, if there is no desktopinfo.ini file, it will copy the sample over and start using it. This makes it transparent for new users. Similarly, the packaged language files are in the "sample-languages" directory. If you decide to use one of the sample language files, you should copy it to a new location first to avoid it being overwritten by the next new version.

Change 15: I've greatly pared down the sample ini file because, well, it's just a sample and there's too many options and items to include everything. Good thing there's a proper manual now to see what's available.

Change 16: Added mtu option to [NETPACKETS](#) and [NETPACKETSRATE](#).

Change 17: Added basic [Windows Event Logs](#) logging.

Change 18: Fixed "InetNtopw not found ws2_32.dll" bug running under Windows XP.

Change 19: Skip some [NETWORKINTERFACES](#) values not available under Windows XP.

Change 20: Added [logo-align](#) to options.

Change 21: Added queue length to [CPU](#) item.

Version v1.10.1

November 2018

Change 1: Fixed bug with logo not updating after ini change.

Change 2: Fixed bug with not aligning correctly when the 'bottom' option is used.

Change 3: Fixed contextmenu option not working.

Change 4: More work converting internal routines to Unicode.

Change 5: I believe I've resolved the stability issues. If you leave the "log-level=error" option on in the ini, you'll see when an error occurs and hopefully the reason.

Version v1.10.2

November 2018

Change 1: Fixed bug with FIXEDDISK and NETWORKADAPTER spinning out of control under Chinese Windows.

Change 2: Continue the Unicode work.

Change 3: Added reference English language file.

Change 4: Fixed handle leak in ProcessMem, TopProcess and registry routines.

Change 5: Fixed bug in bar chart when only one data point is available.

Version v1.11.0

December 2018

There are two important architectural changes in this release: I've moved the data collection code into a thread to allow the gui to be more responsive. This has the side effect of raising the memory footprint slightly. Secondly, I've added a background process to collect 64 bit metrics. This is controlled from the ini file. Plus a bunch of new stuff to explore.

Change 1: Fixed a couple of pointer leaks in options loading and registry/event/file watchers.

Change 2: Changed load model for a couple of DLLs which were causing issues.

Change 3: Added counter option to [TOPPROCESSMEM](#).

Change 4: Added private usage to [PROCESSMEM](#).

Change 5: Introducing the [DesktopInfo64](#) tool. This tool runs silently and allows me to retrieve 64 bit counters and other metrics not available to 32 bit applications.

Change 6: Fixed startup failure on Windows 2000.

Change 7: Added hexadecimal [number format](#) option.

Change 8: Updated reference English language file. If you are a translation contributor please check out your language file to ensure it's accurate and up to date.

Change 9: Added the [BIT](#) display format.

Change 10: Added host option to the [REG](#) and [REGEXIST](#) items.

Change 11: Added support fields to [OEMINFO](#).

Change 12: Added the [monitor-mode](#) option. This gives the option of using Primary Monitor mode or Virtual Screen mode. Previously DTI was using the Primary Monitor mode and this remains the default mode.

Change 13: Added [navigation buttons](#). This really highlighted how unresponsive the gui was so...

Change 14: Added data collection thread to make the gui more responsive. Because of this separation, I've returned the application priority class to idle.

Change 15: More Unicode work in the ini file.

Change 16: Moved the [options] text strings into their own [\[text\] section](#). You will need to move your 'noresults' option to this new section in order for it to be recognised. See the sample ini.

Change 17: Added 'error' [text string](#).

Change 18: Added [SESSIONID](#) and [RDSSESSIONID](#).

Change 19: Changed the TOPPROCESSCPU algorithm to be more accurate.

Change 20: Fixed bug where DTI was responding to Alt+F4 meant for another application.

Change 21: Added [text-editor](#) option.

Version v1.12.0

January 2019

This release has no major architectural changes, yay! There's some minor tweaks to smooth out the navigation buttons and paging, some new tools and bug fixes and a change to how monitor-mode works. If you use the monitor-mode option you'll need to check out the changes.

Change 1: Fixed [REGISTRY](#) so it can read "read only" keys.

Change 2: Now responds to display changes and hopefully also remote desktop display changes.

Change 3: Added the [IF](#) item. See [Conditional Visibility](#) for a full description.

Change 4: Added the '[hidden](#)' common option to items. This allows you to retrieve data without necessarily displaying it. The SET and IF items are hidden by default. Useful for building composite items and doing conditional visibility.

Change 5: Fixed incorrect form height when using navigation buttons in "form" mode (/f).

Change 6: Fixed flickery navigation buttons.

Change 7: Added [text-align](#) option to [options].

Change 8: I've changed monitor-mode so that in virtual screen mode, the origin (top=0, left=0) is the top left of the virtual screen world rather than the top left of the primary monitor. You should review the [size and position](#) description to understand how it works now.

Change 9: Added [monitor-num](#) so we can place Desktop Info on a specific monitor. This option is not used when monitor-mode=1.

Version v1.13.0

February 2019

Change 1: Added [line-spacing](#) to [options]. This controls the number of pixels between rows so you can squeeze it closer together or spread it out.

Change 2: Fixed csv bug duplicating header cells.

Change 3: Added maxrows and %rowcount% to the [WMI](#) item. In addition to limiting the output of the WMI display, it also provides a way to display just the row count rather than all the rows. Keep in mind this still requires a full parse of the result set so a large WMI query will take some time to process even if just getting a row count.

Change 4: Added the [text-offset](#) common option to all items. The *offset* option of the [NETWORKADAPTER](#) and [FIXEDDISK](#) child items has been removed and they now have a default text-offset of 10 pixels. You can set this to any number to adjust the offset or 0 if you don't want an offset.

Change 5: Fixed the offset bug in right aligned and right-to-left text.

Change 6: Added rgb option to [item colours](#).

Change 7: In WMI queries, CIM_DATETIME fields are automatically split into the date and time components so you can format them properly in the display template. See [WMI Date/Time Formatting](#).

Change 8: Added a sample 'advanced' ini file with multiple pages. You can either rename it to the main ini file, desktopinfo.ini or add it as a command line parameter: desktopinfo.exe /ini=desktopinfo-advanced.ini.

Change 9: Fixed header bug in [VIRTUALMEMORY](#) csv and added free and percent free to results.

Change 10: Fixed header bug [PAGEFILE](#) csv and added free and percent free to results.

Change 11: Added free and percent free to [PHYSICALRAM](#).

Change 12: If there is one option on the command line with no '/' prefix, it is assumed to be an ini file. This way you can drag an ini file onto the exe file to start Desktop Info using that ini file.

Change 13: Added 'pages read from disk per second' and 'pages written to disk per second' to [PAGEFAULTS](#).

Change 14: Allow the [bar charts](#) to be on their own row so that they are full width. Add two pipe symbols to the end of the display template.

Change 15: Added the [bar-colors](#) option to customise the bar chart colors.